

Guam Community College
Bid no.: GCC-FB-23-009
Multimedia Projectors and Flat Screen Smart TV

Vendor Information:

Contact: Kevin Tagey

Company: COMPacific

Address: 1900 Army Drive Suite 106 Dededo GU USA 96929

Tel: (671) 637-6677

Fax: (671) 637-6671

Email: kevin@compacific.com

Item #1.A: Projector - Epson Brightlink 735Fi **QTY: 1+ Indefinite** **Price: \$3,483.95**

<input checked="" type="checkbox"/>	Projecting Method: Front/rear/wall mount/table
<input checked="" type="checkbox"/>	Pixel Number: 2,073,600 dots (1920 x1080) x 3
<input checked="" type="checkbox"/>	Color Brightness: (Color Light Output) 3,600 lumens
<input checked="" type="checkbox"/>	White Brightness: (White Light Output) 3,600 lumens
<input checked="" type="checkbox"/>	Aspect Ratio: 2,073,600 dots (1920x1080)
<input checked="" type="checkbox"/>	Native Resolution: Full HD 1080p resolution (1920x1080p)
<input checked="" type="checkbox"/>	Lamp or Laser light
<input checked="" type="checkbox"/>	Size (projected distance): 67" - 120" [0.37m - 0.70m] (Zoom: Wide) 16:9, 60" - 110" [0.37m - 0.69m] (Zoom: Tele) 16:6
<input checked="" type="checkbox"/>	Keystone Correction Manual: Horizontal: ± 3 degrees; Vertical ± 3 degrees
<input checked="" type="checkbox"/>	Dynamic Contrast Ration: Over 2,500,000:1
<input checked="" type="checkbox"/>	USB Plug 'n Play: Projector is compatible with PC and Mac Computers
<input checked="" type="checkbox"/>	Color Reproduction: Up to 1.07 billion colors
<input checked="" type="checkbox"/>	Projection Lens: Type Digital zoom, Focus (Manual), F-Number 1.6, Focal Length 3.7mm, Zoom Ratio Digital zoom 1.0 - 1.35
<input checked="" type="checkbox"/>	Throw Ratio Range: 0.26 (Zoom: Wide), 0.36 (Zoom: Tele)
<input checked="" type="checkbox"/>	Interfaces, Minimum: 2x HDMI (with CEC Control), 1x USB Connector Type A: For saving & reading data & docs 1x Wired LAN RJ-45, Wireless display connect (Wi-Fi or Bluetooth)
<input checked="" type="checkbox"/>	Wireless LAN Port: Minimum 802.11 b/g/n/ac: IEEE 802.11 b: 11 Mbps (2.4 GHz), IEEE 802.11 g: 54 Mbps (2.4 GHz), IEEE 802.11 n: 72.2 Mbps (2.4 GHz) IEEE 802.11 a: 54 Mbps (5 GHz), IEEE 802.11 n: 150 Mbps (5 GHz), IEEE 802.11 ac: 325 Mbps (5 GHz)
<input checked="" type="checkbox"/>	US Standard Power Supply Voltage: 100-240 $\pm 10\%$ 50/60 Hz W/ power cord.
<input checked="" type="checkbox"/>	Security Lockable such as: Cable, Bar, Anchor, etc.
<input checked="" type="checkbox"/>	20" HDMI to HDMI cable
<input checked="" type="checkbox"/>	Software / Hardware Drivers
<input checked="" type="checkbox"/>	Wall mount surge protector: Input power 1200W, Max line current 15A, Network Frequency 50/60 Hz ± 5 Hz auto-sensing Max input current capacity 15A, number of power socket outlets minimum 2, outlet standard NEMA 5-15R, Surge energy rate 1080 joule
<input checked="" type="checkbox"/>	Mounting Bracket: (Screws, Anchors, etc. for wood and concrete)
<input checked="" type="checkbox"/>	Mounting and Installation
<input checked="" type="checkbox"/>	1 year parts and labor warranty

Warranty begins on date of delivery and vendor agrees to resolve problems under six (6) business days, starting from time of GCC service request and must provide equal or better replacement if unable to meet six-day response and resolution timeframe. Part(s) for repair or full unit replacement must be completed according to earliest availability possible, but with confirmation of delivery date provided to GCC within the six-day response period

Guam Community College
Bid no.: GCC-FB-23-009
Multimedia Projectors and Flat Screen Smart TV

Vendor Information:

Contact: Kevin Tagey

Company: COMPacific

Address: 1900 Army Drive Suite 106 Dededo GU USA 96929

Tel: (671) 637-6677

Fax: (671) 637-6671

Email: kevin@compacific.com

Item #1.B: Projector - Epson PowerLite L630U QTY: 1+ Indefinite Price: \$4,482.94

<input checked="" type="checkbox"/>	Projecting Method: Front/rear/wall mount/table
<input checked="" type="checkbox"/>	Pixel Number: 2,304,000 dots (1920 x 1200) x 3
<input checked="" type="checkbox"/>	Color & White Brightness: Output: 5,500 lumens
<input checked="" type="checkbox"/>	Aspect Ratio: 16:10
<input checked="" type="checkbox"/>	Resolution: 1920 x 1200
<input checked="" type="checkbox"/>	Resize: 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050
<input checked="" type="checkbox"/>	Throw Ratio Range: 1.38 (Zoom: Wide), 2.28 (Zoom: Tele)
<input checked="" type="checkbox"/>	Size – projected distance:50” – 300” (1.46m – 8.95m) (Zoom: Wide)
<input checked="" type="checkbox"/>	Keystone Correction:Vertical ±30 degrees, Horizontal: ±20 degrees
<input checked="" type="checkbox"/>	USB Plug 'n Play: Projector is compatible withPC and Mac Computers
<input checked="" type="checkbox"/>	Contrast Ratio: Up to 15,000:1
<input checked="" type="checkbox"/>	Color Reproduction: Up to 1.07 billion colors
<input checked="" type="checkbox"/>	Projection Lens Minimum: 1. Type Digital zoom (Manual)/Focus (Manual), 2. F-Number 1.5-2.0, 3. Focal Length 23.0 - 38.4mm, 4. Zoom Ratio 1.0 - 1.6
<input checked="" type="checkbox"/>	Interfaces, Minimum: 2x HDMI (with CEC Control), 1x USB Connector Type A: For saving & reading data & docs, 1x USB Connector Type B: For USB Display, 1x Wired LAN RJ-45, Wireless display connect (Wi-Fi or Bluetooth)
<input checked="" type="checkbox"/>	Wireless LAN Port: Minimum 802.11 b/g/n/ac IEEE 802.11 b: 11 Mbps (2.4 GHz), IEEE 802.11 g: 54 Mbps (2.4 GHz), IEEE 802.11 n: 72.2 Mbps (2.4 GHz) IEEE 802.11 a: 54 Mbps (5 GHz), IEEE 802.11 n: 150 Mbps (5 GHz), IEEE 802.11 ac: 325 Mbps (5 GHz)
<input checked="" type="checkbox"/>	US Standard Power Supply Voltage: 100 – 240 +10%, 50/60 Hz W/ power cord
<input checked="" type="checkbox"/>	Security Lockable such as: Cable , Bar, Anchor, etc.
<input checked="" type="checkbox"/>	Wireless Remote Control: Power, Source Search, Menu function
<input checked="" type="checkbox"/>	20' HDMI to HDMI cable
<input checked="" type="checkbox"/>	Software / Hardware Drivers
<input checked="" type="checkbox"/>	Wall mount surge protector: Input power 1200W, Max line current 15A, Network Frequency 50/60 Hz +/-5 Hz auto-sensing Max input current 15A, Switching current capacity 15A, number of power socket outlets minimum 2, Outlet standard NEMA 5-15R, Surge energy rate 1080 joule
<input checked="" type="checkbox"/>	Mounting Bracket: (Screws, Anchors, etc. for wood and concrete)
<input checked="" type="checkbox"/>	Mounting and Installation
<input checked="" type="checkbox"/>	1 year parts and labor warranty

Warranty begins on date of delivery and vendor agrees to resolve problems under six (6) business days, starting from time of GCC service request and must provide equal or better replacement if unable to meet six-day response and resolution timeframe. Part(s) for repair or full unit replacement must be completed according to earliest availability possible, but with confirmation of delivery date provided to GCC within the six-day response period

Guam Community College
Bid no.: GCC-FB-23-009
Multimedia Projectors and Flat Screen Smart TV

Vendor Information:

Contact: George Ilaio

Company: JMI Edison

Address: 130 Siket St. Harmon Industrial Park Harmon, Guam 96913

Tel: (671) 664-1256

Fax: (671) 649-5685

Email: georgeilao@jmiguam.com

Item #2: Flat Screen Smart TV Samsung AU8000 QTY: 1+ Indefinite Price: \$2,031.28

<input checked="" type="checkbox"/> Screen Size: Minimum 74.5" Measured Diagonally
<input checked="" type="checkbox"/> Minimum Video: 4K Picture Processor, HDR (High-Dynamic Range), Resolution 3,840 x 2,160
<input checked="" type="checkbox"/> Minimum Wireless Connectivity: Wi-Fi 802.11ac, Wi-Fi Direct, Bluetooth 4.2
<input checked="" type="checkbox"/> Wired ethernet connection
<input checked="" type="checkbox"/> Minimum Wired Connection: 1 USB port, 1 HDMI Port
<input checked="" type="checkbox"/> Wired and Wireless Screen Mirroring via: Windows, Apple, Android
<input checked="" type="checkbox"/> TV Remote Control, wireless
<input checked="" type="checkbox"/> US standard Power cord: AC 110-120V 15amps
<input checked="" type="checkbox"/> 1 year parts and labor warranty
<input checked="" type="checkbox"/> Flat Screen TV Wall Mount
<input checked="" type="checkbox"/> Mounting and Installations
<input checked="" type="checkbox"/> Full Motion TV Mount: Swivel range 120° minimum, Tilt range +5°/-15° minimum, TV size: Minimum 75 inches, Max Load: Minimum 100 pounds weight
<input checked="" type="checkbox"/> 20' HDMI to HDMI cable
<input checked="" type="checkbox"/> Wall mount surge protector: Input power 1200W, Max line current 15A, Network Frequency 50/60 Hz +/-5 Hz auto-sensing Max input current 15A, Switching current capacity 15A, number of power socket outlets minimum 2, Outlet standard NEMA 5-15R, Surge energy rate 1080 joule

Warranty begins on date of delivery and vendor agrees to resolve problems under six (6) business days, starting from time of GCC service request and must provide equal or better replacement if unable to meet six-day response and resolution timeframe. Part(s) for repair or full unit replacement must be completed according to earliest availability possible, but with confirmation of delivery date provided to GCC within the six-day response period